

• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.  
 • PPE inspection should be conducted with the manufacturer's Instructions for Use.  
 Download the instructions at [PETZL.COM](http://PETZL.COM).



# PROGRESS CAPTURE PULLEY

## User information

Surname

Address

Identifier

## PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

**Manufacturer:** Petzl, ZI Cidex 105A - 38920 Croles - France

<input checked="" type="radio"/> Good condition (G)	<input type="radio"/> To monitor (TM)	<input type="radio"/> To repair (TR)	<input type="radio"/> Do not use, retire (R)	<input type="radio"/> N/A Not applicable
---	---------------------------------------	--------------------------------------	--	---

### 1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	N/A
----------------------------------	-----------------------	-----------------------	-----------------------	-----------------------	-----

### 2. Preliminary observations

Verify the presence and legibility of the serial number and the CE mark.  
 Verify that the product lifetime has not been exceeded.  
 Compare with a new device to verify there are no modifications or missing elements.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

### 3. Checking the condition of the side plates

- Check the condition of the moving side plates (deformation, cracks, marks, wear, corrosion).
- Check the condition of the attachment hole (deformation, cracks, marks, wear, corrosion).
- If applicable, check the condition of the auxiliary attachment hole (deformation, cracks, marks, wear, corrosion).
- Check the condition of the rivets (deformation, cracks, marks, wear, corrosion, lack of play).
- Verify that the side plates rotate properly.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

### 4. Checking the side plates' opening and locking systems

- Check the condition and function of the locking system (deformation, cracks, marks, wear, dirt, effectiveness of the return spring(s)).

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

### 5. Checking the cam

- Check the condition of the gate (deformation, cracks, marks, wear, corrosion, absence of foreign bodies). Check that all teeth are present and check their state of wear. The teeth must not be dirty. If necessary, clean them with a brush.
- Check the cam's rotation and the effectiveness of the return spring.
- Verify that the cam catch is working properly.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

### 6. Checking the sheave

- Check the condition of the sheave (deformation, cracks, marks, wear, corrosion, absence of foreign bodies).
- Verify that the sheave turns freely in both directions.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

### 7. Function check

- Install your pulley on an anchor and install a compatible rope around the sheave.
- With the cam deactivated, circulate the rope in both directions.
- With the cam activated, make sure the rope circulates in one direction and blocks in the other direction.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

### Comments (detail here any defects found on the product and accomplished tasks)

### VERDICT

- Product **fit** to remain in service
- Product **unfit** to remain in service

Inspected by

Company

Date  Next inspection date