

• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 • PPE inspection should be conducted with the manufacturer's Instructions for Use.
 Download the instructions at PETZL.COM.



JAG SYSTEM

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France

<input checked="" type="radio"/> Good condition (G)	<input type="radio"/> To monitor (TM)	<input type="radio"/> To repair (TR)	<input type="radio"/> Do not use, retire (R)	<input type="radio"/> N/A Not applicable
---	---------------------------------------	--------------------------------------	--	---

1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	N/A
----------------------------------	-----------------------	-----------------------	-----------------------	-----------------------	-----

2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new device to verify there are no modifications or missing elements.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

3. Removing the connectors and the cover

- Remove the connectors and inspect them using the corresponding inspection procedure.
- Collapse the cover.
- Inspect JAG and JAG TRAXION using the corresponding inspection procedures.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

4. Inspecting the rope

- Check the condition of the sewn loop on the JAG TRAXION.
- Move this loop to inspect the hidden parts of the JAG TRAXION attachment hole.
- Check the condition of the sheath over the full length of the rope (cuts, wear, burns, fuzzy areas or signs of chemical products...).
- Do a tactile inspection of the core along the full length of the rope (hard spots, swelling, soft or crushed areas...).
- Check the stitching. Make sure there are no cut, torn, loose, or worn threads.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

5. Inspecting the cover

- If necessary, remove the cover and replace it with a JAG SYSTEM replacement cover.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

6. Installing the connectors

- Check that the rope is not tangled before reassembling the system.
- Reinstall the connectors.
- Verify that the connectors are correctly positioned in the JAG and JAG TRAXION attachment holes.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

7. Function check

- Install your JAG SYSTEM on an anchor at low height, with a light load.
- Verify that the system locks under load.
 - Verify that the JAG TRAXION can be deactivated for a short descent.
 - Verify that the load can be hauled.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT

Product **fit** to remain in service

Product **unfit** to remain in service

Inspected by

Company

Date Next inspection date