

• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 • PPE inspection should be conducted with the manufacturer's Instructions for Use.
 Download the instructions at PETZL.COM.



WIRE STROP

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France

<input checked="" type="radio"/> Good condition (G)	<input type="radio"/> To monitor (TM)	<input type="radio"/> To repair (TR)	<input type="radio"/> Do not use, retire (R)	<input type="radio"/> N/A Not applicable
---	---------------------------------------	--------------------------------------	--	---

1. Known product history
 Any PPE showing unexpected degradation should be quarantined, pending a detailed inspection.
 The user should:
 - Provide precise information on the usage conditions.
 - Report any exceptional event regarding his/her PPE.
 (Examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...).

<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	N/A
----------------------------------	-----------------------	-----------------------	-----------------------	-----------------------	-----

2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new product to verify there are no modifications or missing parts.

3. Checking the condition of the cable and the sheath

- Check the condition of the sheath along its entire length (marks, holes, tearing, discoloration).
- Check the condition of the cable along its entire length: marks, deformation, corrosion...

4. Checking the carabiner attachment hole

- Check the condition of the protective sleeve (cracks, deformation...).
- Move the sleeve to check the condition of the thimble and the cable around the attachment hole: marks, wear, cracks, deformation, corrosion...
- Replace the sleeve before returning the product to service.

5. Checking the attachment loop

- Check the condition of the protective sleeve (cracks, deformation...). Unscrew the plug so the sleeve can be moved.
- Check the condition of the cable and the sheath around the attachment loop: marks, wear, cracks, deformation, corrosion...
- Replace the sleeve and tighten the plug before returning the product to service.

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT

Product **fit** to remain in service

Product **unfit** to remain in service

Inspected by

Company

Date Next inspection date